

Mechanical characteristics
cable group

Mechanische Eigenschaften
Kabelgruppe

G 2: 0.6/3.7; 0.6L/3.7; 0.6L/3.7AF Draka; 3C-2V;
75022 V(0.6L/3.7) Sytronic Kabel GmbH;
75060 V(0.6/3.7) Sytronic Kabel GmbH;
8241 Belden; KX 6A; RG-59B/U;
VK95 0.6/3.7 Percon
G39: 0.8/3.7 AF Draka; 0.8/3.7C Bedea;
1505A Belden HDTV; Image 720 Argosy;
75080 AFZ 4-S Midi 0.8/3.7 Sytronic;
Telass 80 Bedea; VPM2000 Gepco;
VK6/0.8 FRLS 0.8/3.7 Percon
RG-62A/U

interface dimensions acc. to
assembly code
panel piercing
centre conductor
outer conductor
mating life

Steckgesicht nach
Montageanleitung
Montagebohrung
Innenleiter
Außenleiter
Steckzyklen

IEC 61169-8
A10
Z005
solder/löt
clamp/klemm
≥500

Components

centre contact
outer contact
other metal parts
insulator
gasket

Bauteile

Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung
Dichtung

Materials / Material

CuBe2
CuZn39Pb3
CuZn39Pb3
PTFE
silicone / Silikon

Finish / Oberfläche

Ni2Au0,8
Cu2Ni5
Cu2Ni5

Electrical characteristics

impedance
frequency
voltage proof
insulation resistance
contact resistance
centre contact
outer contact


Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Prüfspannung
Isolationswiderstand
Durchgangswiderstand
Innenkontakt
Außenkontakt

75 Ω
0-4 GHz
1,5kV_{eff} / 50 Hz
≥ 5 GΩ

≤ 20 mΩ
≤ 5 mΩ

M 1:1



Environmental
RoHS compliant

Umgebung
RoHS konform

2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]	
			gez./ drawn	17.10.2018	MA		
			gepr./ appr.	26.10.2018	HR	ca./approx. 17	
			Maßstab/ scale 2:1 (1:1)	Benennung/ title BNC Panel Jack BNC-Kabeleinbaubuchse			
			untol. Maße/ dim. without tolerances according to	Untert./ doc. type K	Zeichnungsnr./ drawing no. J01003A0012		Maße/ dimensions: mm
			Ersatz für/ replaces				Original : DIN A4 Blatt/ sheet 1 von/ of 1