



Mechanical characteristics

cables

interface dimensions acc. to assembly code

center conductor
outer conductor

mating life

Components

center contact
outer contact
outher metal parts
insulator
gasket

Electrical characteristics

impedance
frequency
working voltage
voltage proof
insulation resistance

contact resistance
center contact
outer contact

Environmental

operating temp.
RoHS compliant

Mechanische Eigenschaften

Kabel

Steckgesicht nach Montageanleitung

Innenleiter
Außenleiter

Steckzyklen

Bauteile

Innenkontakt
Außenkontakt
sonstige Metallteile
Isolierung
Dichtung

Elektrische Eigenschaften

Wellenwiderstand
Frequenz
Betriebsspannung
Prüfspannung
Isolationswiderstand

Durchgangswiderstand
Innenkontakt
Außenkontakt

Umgebung

Betriebstemperatur
RoHS konform

Cable group / Kabelgruppe G10 (UT-141):

- (b) 1673A BELDEN = SM 1168A BELDEN alt, EZ 141 SUHNER, Flexiform 402 NM Habia Cable,
- (c) RG-402/U, SUCOFORM 141 SUHNER, UT-141 MICRO-COAX

- (c) IEC 60169-17 A12 solder / löt solder / löt >500

Materials / Material

brass / Messing
brass / Messing
brass / Messing
PTFE
silicone/Silikon

Finish / Oberfläche

NiP-Au
Ag2CuSnZn0,5 (d)
Cu2Ni5

50 Ω
0-11 GHz
≤ 500 V_{eff} / 50 Hz
1,5 kV_{eff} / 50 Hz
≥ 5 GΩ

≤ 10 mΩ
≤ 2,5 mΩ

- (c) -40 °C / +155 °C
2011/65/EU

M 1:1



Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	gez./ drawn	Datum/ date	Name/ name	Gewicht/ weight (g)	
					01.07.2014	KL		
				gepr./ appr	02.07.2014	BJ	ca./approx.	
				Maßstab/ scale	Benennung/ title			
				5:1	TNC Straight Plug TNC-Kabelstecker			
d	25923	01.07.2014	KL	untol. Maße/ dim. without tolerances according to	Unterl./ doc. type	Zeichnungsnr./ drawing no.		
c	22630	25.11.2011	MA	K				J01010A0021
b	6331	18.01.1995	BJ	Ersatz für/ replaces				Zeichnung vom 14.12.1989
a	3926	24.07.1992	HM					
							Maße/ dimensions: mm	
							Original : DIN A4	
							Blatt/ sheet 1 von/ of 1	

