



panel piercing/
Montagebohrung:
Z119

Mechanical characteristics

cables

interface dimensions acc. to

assembly code

centre conductor

outer conductor

mating life

engagement force

disengagement force

Components

centre contact

outer contact

insulator

Electrical characteristics

impedance

working voltage

voltage proof

insulation resistance

contact resistance

centre contact

outer contact

Environmental

operating temp.

RoHS compliant

Mechanische Eigenschaften

Kabel

Steckgesicht nach

Montageanleitung

Innenleiter

Außenleiter

Steckzyklen

Steckkraft

Ziehkraft

Bauteile

Innenkontakt

Außenkontakt

Isolierung

Elektrische Eigenschaften

Wellenwiderstand

Betriebsspannung

Prüfspannung

Isolationswiderstand

Durchgangswiderstand

Innenkontakt

Außenkontakt

Umgebung

Betriebstemperatur

RoHS konform

cable group / Kabelgruppe G11 (UT-85):
1671A; EZ 86; RG-405/U; Sucoform 86; UT-85

MIL-STD-348A
Limited Detent

C32

solder / löt

solder / löt

≥500

max. 45 N

min. 9 N

Materials / Material

Brass / Messing

Brass / Messing

PTFE

Finish / Oberfläche

NiP-Au

NiP-Au

50 Ω
≤ 335V_{eff} / 50 Hz
500 V_{eff} / 50 Hz
≥ 5 GΩ

≤ 6 mΩ
≤ 2 mΩ

-55°C / +155°C
2002/95/EC



M 1:1

				2007	Datum/ date	Name/ name	Gewicht/ weight [g]	Oberfläche/ surface [mm ²]	Werkstoff/ material
				gez./ drawn	13.11	HR			
				gepr./ appr.	06.12.07	SP			Oberfläche/ finish
				Norm/ stand.					
				Maßstab/ scale 5:1 (1:1)	Benennung/ title SMP Bulkhead Plug, male SMP-Kabeleinbaustecker				
				untol. Maße/ dim. without tolerances according to	Untert./doc. type K	Zeichnungsnr./ drawing no. J01390A0011			Maße/ dimensions: mm
Änd./ rev. Index	Änderungsmittelung/ revision code	Datum/ date	Name/ name	Ersatz für/ replaces			Original : DIN A4 Blatt/ sheet 1 von/ of 1		